

Rapid crack propagation in disordered brittle solids

Nitin Gupta¹, Laure Chomat², Cindy L Rountree³, Daniel Bonamy⁴

¹ University Paris-Saclay, CNRS, CEA Saclay, SPEC, SPHYNX, 91191, Gif-sur-Yvette, France, France.
viratnitinvarshney@gmail.com

² University Paris-Saclay, CNRS, CEA Saclay, SPEC, SPHYNX, 91191, Gif-sur-Yvette, France, France.
laure.chomat@cea.fr

³ University Paris-Saclay, CNRS, CEA Saclay, SPEC, SPHYNX, 91191, Gif-sur-Yvette, France, France.
cindy.rountree@cea.fr

⁴ University Paris-Saclay, CNRS, CEA Saclay, SPEC, SPHYNX, 91191, Gif-sur-Yvette, France, France.
daniel.bonamy@cea.fr

Paper ID: 304

[Symposium S8: Fracture, and damage of materials](#)

Abstract

Understanding dynamic fracture in brittle solids is a fundamental aspect of materials science, with implications for engineering, geophysics, and advanced manufacturing. Linear Elastic Fracture Mechanics (LEFM) provides the relevant framework to evaluate quantitatively the mechanical energy flux released to the tip of a growing crack and subsequently to predict fracture speed [1]. Still, observations revealed different instabilities occurring at high speed, which render the problem more complex. In particular, it has been observed in amorphous polymers [2, 3] that crack growth can suddenly switch from a slow-speed regime (<cm/s) to a fast-speed regime (>100m/s), which cannot be explained within conventional LEFM [4]. The present research intends to shed light on this instability by experimentally studying the mode-I fracture and crack velocity that develop during the dynamic failure of brittle solids, such as polymethylmethacrylate (PMMA, classically considered the archetype of brittle amorphous materials) and artificial rocks (heterogeneous materials made of sintered glass beads). Crack speed is measured by potential drop methods, and meso-scale dissipation and damage processes are inferred from morphological analysis of fracture surfaces. The transition between the slow and fast fracture regimes will be characterized, and the role played by damage processes occurring at the fracture process zone scale will be discussed. [1] Freund

LB, Freud L. Dynamic fracture mechanics. Cambridge University Press; 1998. [2] Ravi-Chandar K, Balzano M. On the mechanics and mechanisms of crack growth in polymeric materials. Engineering fracture mechanics. 1988;30(5):713-27. [3] Vincent-Dospital T, Toussaint R, Santucci S, Vanel L, Bonamy D, Hattali L, et al. How heat controls fracture: the thermodynamics of creeping and avalanching cracks. Soft Matter. 2020;16(41):9590-602. [4] Heinzmann R, Seghir R, Alam SY, R'ethor'e J. Experimental investigation of the alternate recurrence of quasi-static and dynamic crack propagation in PMMA. International Journal of Fracture. 2023;242(2):227-45.

Keywords:

Dynamic Fracture mechanics Brittle solids Energy release rate (ERR) Crack growth